

according to Regulation (EC) No 1907/2006

Stabiloplast Resin 448 0003

Revision date: 03.12.2020 Product code: 4480003 Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Stabiloplast Resin 448 0003

Further trade names

contained in: 448 0004 Stabiloplast Set

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives, sealants

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name: Renfert GmbH
Street: Untere Giesswiesen 2
Place: D-78247 Hilzingen

Telephone: +49 7731 8208-0 Telefax: +49 7731 8208-70

e-mail: info@renfert.com
Contact person: Frau Andris

e-mail: silke.andris@renfert.com

Internet: www.renfert.com

1.4. Emergency telephone number: GB: 0044 151 951 3317 (Health and Safety Executive (HSE) Chemicals) | USA:

800-222-1222 (National Poison Control number) | CA: British Columbia: 800-567-8911 or 604-682-5050 Alberta: 1-800-332-1414 or 944-1414 Saskatchewan: 1-866-454-1212 Manitoba: 1-855-776-4766 Ontario: 1-800-268-9017 Quebec: 1-800-463-5060 New Brunswick: 911 New Foundland: 1-866-727-1110 Northwest Territories: 1-800-332-1414 Nova Scotia: 1-800-565-8161 | AU: 13 11 26 | ZA: 021 938 6084 (Office Hours) or 021

931 6129 (24 Hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

ethyl 2-cyanoacrylate

Signal word: Warning Pictograms:



Hazard statements

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves and eye/face protection.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P337+P313 If eye irritation persists: Get medical advice/attention.

Special labelling of certain mixtures

EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.





according to Regulation (EC) No 1907/2006

Stabiloplast Resin 448 0003

Revision date: 03.12.2020 Product code: 4480003 Page 2 of 7

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Cyanoacrylate containing adhesive.

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	GHS Classification	•	•		
7085-85-0	ethyl 2-cyanoacrylate				
	230-391-5	607-236-00-9	01-2119527766-29		
	Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H315 H319 H335				
123-31-9	1,4-dihydroxybenzene				
	204-617-8	604-005-00-4	01-2119524016-51		
	Carc. 2, Muta. 2, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1B, Aquatic Acute 1 (M-Factor = 10), Aquatic Chronic 1 (M-Factor = 10); H351 H341 H302 H318 H317 H400 H410				

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off contaminated clothing and wash it before reuse.

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

After contact with skin

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder, Carbon dioxide (CO2), alcohol resistant foam, Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to the escape of irritating gases and vapours.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protection equipment.

Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Allow stiffening. Take up mechanically.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8





according to Regulation (EC) No 1907/2006

Stabiloplast Resin 448 0003

Revision date: 03.12.2020 Product code: 4480003 Page 3 of 7

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Handle and open container with care.

Use only in well-ventilated areas.

Avoid contact with eyes and skin.

When using do not eat, drink or smoke.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Further information on handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place.

Keep container tightly closed.

Hints on joint storage

No special measures are necessary.

Further information on storage conditions

storage temperature: 6 - 15°C

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity.

7.3. Specific end use(s)

Please refer to our internet website for more information: www.renfert.com

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
7085-8	-0 Ethyl cyanoacrylate	0.3	1.5		STEL (15 min)	WEL
123-3	-9 Hydroquinone	-	0.5		TWA (8 h)	WEL

8.2. Exposure controls

Appropriate engineering controls

Safe handling: see section 7

Protective and hygiene measures

Do not breathe vapour.

Avoid contact with skin, eyes and clothes.

Wash hands before breaks and after work.

Keep away from food, drink and animal feedingstuffs.

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber)
Thickness of the glove material: 0,5 mm

Breakthrough time: > 30 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Respiratory protection

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

Respiratory protection necessary at: insufficient ventilation

Environmental exposure controls

Do not allow to enter into surface water or drains.

Renfert GmbH

Test method



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Stabiloplast Resin 448 0003

Revision date: 03.12.2020 Product code: 4480003 Page 4 of 7

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: blue

Odour: characteristic

pH-Value: not applicable

Changes in the physical state

Melting point: not determined

Initial boiling point and boiling range: 150 °C Literaturwert
Flash point: 87 °C DIN 51758

Flammability

Solid: not applicable
Gas: not applicable

Explosive properties

not explosive according to EU A.14

Lower explosion limits:

Upper explosion limits:

Ignition temperature:

not determined
not determined
not determined

Auto-ignition temperature

Solid: not applicable
Gas: not applicable
Decomposition temperature: not determined
Vapour pressure: 0.3 hPa

(at 20 °C)

Density: not determined Water solubility: practically insoluble Partition coefficient: not determined Viscosity / dynamic: not determined Viscosity / kinematic: not determined Vapour density: not determined Evaporation rate: not determined Solvent content: 0.0 %

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Violent reaction with: Alcohols, Amines, Alkali (Iye), Acid, Water

10.4. Conditions to avoid

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

Stabiloplast Resin 448 0003

Revision date: 03.12.2020 Product code: 4480003 Page 5 of 7

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
123-31-9	1,4-dihydroxybenzene					
	oral	LD50	375 mg/kg	Rat		OECD 401

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (ethyl 2-cyanoacrylate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The product has not been tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

Further information

Do not allow uncontrolled discharge of product into the environment.

The product has not been tested. Due to the consistency along with the low water solubility of the product a bioavailability is unlikely.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

List of Wastes Code - residues/unused products

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

Other applicable information (land transport)

No dangerous good in sense of these transport regulations.

Marine transport (IMDG)

Other applicable information (marine transport)

No dangerous good in sense of these transport regulations.

Air transport (ICAO-TI/IATA-DGR)



according to Regulation (EC) No 1907/2006

Stabiloplast Resin 448 0003

Revision date: 03.12.2020 Product code: 4480003 Page 6 of 7

Other applicable information (air transport)

No dangerous good in sense of these transport regulations.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3: Flüssige Stoffe oder Gemische, die Kriterien für eine der folgenden in Anhang I der Verordnung (EG)

2004/42/EC (VOC): not applicable

National regulatory information

Water hazard class (D): 3 - strongly hazardous to water

Additional information

REGULATION (EC) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on substances that

deplete the ozone layer: not applicable

REGULATION (EU) 2019/1021 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on persistent organic

pollutants : not applicable

REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the export and

import of hazardous chemicals: not applicable

SECTION 16: Other information

Changes

Abs. 7, 11, 15, 16 * Data changed compared with the previous version

Abbreviations and acronyms

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

CAS: Chemical Abstracts Service (division of the American Chemical Society)

ATE: Acute Toxicity Estimates

LD50: lethal dose, 50%

LC50: lethal concentration, 50%

EC50: half maximal effective concentration

ADR: Accord européen relatif au transport international des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire de marchandises Dangereuses (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

VOC: volatile organic compound(s)

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.





according to Regulation (EC) No 1907/2006

Stabiloplast Resin 448 0003

Revision date: 03.12.2020 Product code: 4480003 Page 7 of 7

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Restricted to professional users.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)